

SAGEMCOM

ADR 622

MULTI-SERVICE NG SDH PLATFORM

- STM-1 / STM-4 Add- Drop Multiplexer
- Secured, Flexible, scalable and fully protected platform
- Transport of Ethernet over SDH (E.O.S)
 - Advanced Ethernet switch features
 - Compact and easy to use solution.



SAGEMCOM INTRODUCES ADR622, STM-1 AND STM-4 MULTI-SERVICE PLATFORM WHICH OFFERS A LARGE VARIETY OF INTERFACES, FROM E1, E3/DS3 TO ETHERNET, FAST ETHERNET AND GIGABIT ETHERNET.

ADR 622 addresses backhauling networks, utilities networks and SDH microwaves networks.

ADR 622 is a fully protected equipment designed to meet all EMC recommendation from utilities network that will need more isolation, magnetic, disturbance protection than telecommunications carriers. Together with FMX and IONOS NMS (Network Management System), it offers utilities customers a fully integrated solution for all their transmission requirements, from interfaces below 64 kbps up to Gigabit Ethernet.

ADR 622 is a flexible non blocking cross-connect for microwave networks, providing STM-1 interfaces every nodes. It will also be fully integrated into Sagemcom solution and managed under the same NMS.

ADR 622 is a scalable solution for 3G, Wimax, DLC and DSL backhauling with its compactness allowing to fit into a street cabinet and in service upgradeability from STM-1 to STM-4.

ADR 622 is part of Sagemcom SDH family which also includes ADR 155c, STM-1 A.D.M., ADR 2500 eXtra, STM-4 / STM-16 A.D.M. and ADR 10000, STM-16 / STM-64 A.D.M. This range, fully managed by IONOS NMS, is sold worldwide either as stand alone equipment or as part of turnkey networks. Sagemcom' capability to offer a complete transmission equipment together with optical fiber, civil works, buildings gives added value to its customers.



TECHNICAL FEATURES

AGGREGATE SIGNALS

- STM-1, STM-4 G.957
- S-1.1, L-1.1, L1.2 opticals SFPs
- Single Fiber optical SFPs
- S-4.1, L-4.1, L-4.2 optical SFPs
- External optical booster for long haul networks

TRIBUTARY SIGNALS

- E1, E3, DS3 G.703
- E1 120 ohms and 75 ohm cards.
- Front access and Line termination Units.
- Ethernet, Fast Ethernet 10/100 Base T
- Gigabit Ethernet 1000 base T, SX, LX and ZX

MECHANICAL SPECIFICATIONS

- ETS 300 119-3 and 4

POWER SUPPLY

- -48 V DC (-36 v to -72 v)

DIMENSIONS

- 6U, 19" and ETSI subracks

CONSUMPTION

- 160 W max, 100 W typical

ENVIRONMENT

- Etsi range +5°C to +45°C
- Etsi extended range -5°C to +55°C

AUXILIARY SIGNALS

- RJ45 Ethernet interface for F and TNM
- E1 and F1 RJ45 interfaces for EOW

MATRIX

- 16 VC4 non blocking cross-connect at VC12, VC3 and VC4 level

PROTECTIONS

- Line Protection, SNCP and MSP G.783
- Card protection (E1, E3/DS3, Controller, Matrix/Power supply)

ETHERNET FEATURES

- GFP150 and GFP2500 cards offer Layer 2 Ethernet Switch :
- GFP, VCAT and LCAS protocols, STP and MSTP protocols
- Customer VLAN and Provider VLAN support

OPERATION

- Embedded HTTP server (Internet Explorer and Mozilla firefox)
- Native SNMP

All rights reserved. The information and specifications included are subject to change without prior notice. Sagemcom Energy & Telecom tries to ensure that all information in this document is correct, but does not accept liability for error or omission. Non contractual document. All trademarks are registered by their respective owners. Simplified joint stock company - Capital 44.824.840 Euros - 518 250 337 RCS Nanterre. 01/2013

Sagemcom Energy & Telecom SAS

Headquarters : 250, route de l'Empereur
92848 Rueil-Malmaison Cedex - FRANCE

Tel : +33 (0)1 57 61 10 00 - Fax : +33 (0)1 57 61 10 01

www.sagemcom.com

SAGEMCOM